



CATEGORY	INDOOR								REMOTE	OUTDOOR			
FEATURE	AP-103H	AP-103	AP-104/105	AP-204/205	AP-114/115	AP-214/215	AP-134/135	AP-224/225	RAP-3WN/RAP-3WNP	RAP-108/109	RAP-155/155P	AP-175P/AP-175AC	AP-274/AP-275
													
<b>NETWORK INTERFACES</b>	1x GE + 2x FE + 1x passthrough RJ-45	1x GE	1x GE	1x GE	1x GE	1x GE	2x GE	2x GE	3x FE	1x GE + 1x FE	5x GE	1x GE	2x GE
<b>JUMBO FRAME SUPPORT ON UPLINK</b>	No	No	No	✓	No	✓	No	✓	No	No	No	No	✓
<b>USB HOST INTERFACE</b>	No	No	No	No	✓	✓	No	✓	✓	✓	✓	No	No
<b>CONSOLE PORT</b>	Header	Header	RJ-45	RJ-45	RJ-45	RJ-45	RJ-45	RJ-45	Header	RJ-45	Header	USB Type A	Micro USB
<b>POE PD POWER</b>	3af	3af	3af	3af	3af/3at	3af/3at	3af	3af/3at	No	3af/at	No	3at	3at
<b>POE PSE</b>	No	No	No	No	No	No	No	No	No/802.3af	No	No/802.3at (1x) or 802.3af (2x)	✓ (AP-175AC)	No
<b>DC POWER SUPPORT</b>	12V	12V	12V	12V	12V	12V	12V	12V	12V / 48V	12V	12V / 54V	N/A	N/A
<b>SHIPS WITH AC-TO-DC ADAPTER</b>	No	No	No	No	No	No	No	No	✓ (cord not included for RAP-3WNP)	No	✓ (cord not included for RAP-155P)	No	No
<b>TEMPERATURE RANGE</b>	0° C to +40° C	0° C to +40° C	0° C to +50° C	0° C to +40° C	0° C to +50° C	0° C to +50° C	0° C to +50° C	0° C to +50° C	0° C to +40° C	0° C to +40° C	0° C to +40° C	-40° C to +50° C	-40° C to +65° C
<b>ENCLOSURE TYPE</b>	Plastic	Plastic	Plastic/metal	Plastic/metal	Plastic/metal	Plastic/metal	Plastic/metal	Plastic/metal	Plastic	Plastic	Plastic	Plastic/metal	Plastic/metal
<b>ENCLOSURE VOLUME (MM)</b>	140 x 86 x 30	150 x 150 x 41.5	132 x 135 x 45	150 x 150 x 41.5	180 x 180 x 45	180 x 180 x 45	170 x 170 x 45	203 x 203 x 54	129 x 109 x 64	181 x 160 x 72	185 x 245 x 65	225 x 225 x 105	230 x 230 x 190 (AP-274) 230 x 240 x 270 (AP-275)
<b>WEIGHT (UNIT ONLY, WITH DESK MOUNT)</b>	260 g	300 g	300 g	380 g	650 g	650 g	760 g	750 g	180 g	460 g	700 g	3,500 g	2,700 g (AP-274) 2,400 g (AP-275)

CATEGORY	INDOOR									REMOTE			OUTDOOR	
FEATURE	AP-103H	AP-103	AP-104/105	AP-204/205	AP-114/115	AP-214/215	AP-134/135	AP-224/225	RAP-3WN/RAP-3WNP	RAP-108/109	RAP-155/155P	AP-175P/AP-175AC	AP-274/AP-275	
														
<b>PLENUM RATED</b>	No	No	✓	✓	✓	✓	✓	✓	No	No	No	No	No	
<b>TAA/FIPS VERSION AVAILABLE</b>	No	No	✓	No	✓	✓	✓	✓	✓	✓	✓	No	No	
<b>LIFETIME WARRANTY</b>	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	No	✓	
<b>MINIMUM SOFTWARE VERSION</b>	ArubaOS 6.4.1.0	ArubaOS 6.4.0.0 InstantOS 4.1.0.0	ArubaOS 3.4.1.0 (AP-105) ArubaOS 6.1.3.0 (AP-104) InstantOS 2.0.0.3	ArubaOS 6.4.1.0 InstantOS 4.1.1.0	ArubaOS 6.3.1.0 InstantOS 4.0.0.0	ArubaOS™ 6.4.2.0 InstantOS™ 4.1.1.0	ArubaOS 6.1.1.0 InstantOS 2.0.0.3	ArubaOS 6.3.0.0 InstantOS 4.0.0.0	ArubaOS 6.1.4.0 InstantOS 3.0.0.0	ArubaOS 6.2.0.0 InstantOS 3.2.0.0	ArubaOS 6.3.0.0 InstantOS 3.3.0.1	ArubaOS 5.0.2.1 InstantOS 2.0.0.3	ArubaOS 6.4.0.0 InstantOS 4.1.0.0	
<b>SPECTRUM ANALYSIS SUPPORT</b>	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
<b>MAXIMUM POWER CONSUMPTION (EXCLUDING USB, POE PSE)</b>	8.3W (DC) 9.4W (PoE)	8W (DC) 9.5W (PoE)	10W (DC) 12.5W (PoE)	11.7W (DC) 12.5W (PoE)	12W (DC) 13W (PoE)	13.6W (DC) 14.9W (PoE)	12W (DC) 13.5W (PoE)	15.5W (DC) 13.5W/17W (PoE)	4.0W/5.5W	12.5W	15.5W	18W	23W	
<b>MAX IPSEC ENCRYPTED WIRED THROUGHPUT (RAP MODE)</b>	10	10	15	20	20	20	40	100	20	20	100	15	20	



1344 CROSSMAN AVE | SUNNYVALE, CA 94089  
 1.866.55.ARUBA | T: 1.408.227.4500 | FAX: 1.408.227.4550 | INFO@ARUBANETWORKS.COM